



- GPS
- 30 CHANNEL GPS
- 4.3" TFT 16:9 DISPLAY
- TOUCH SCREEN
- RS232 PORT
- CE 5.0
C++ or .NET

PN6000 is a standard navigation device with a communication port (serial RS232) that allows the connection to any AVL system.

With its 5.6" touch screen and serial link it is a ideal PND for location base service market.

Running on Windows CE 5.0 its SDK (software Development Kit) is fully open and allows you to implement your own software solution Connected to the cradle. The PN6000 can communicate with peripherals trough a Rx/Tx serial link.

In addition, DVB-T tuner is embedded, a set of antennas is provided for the signal optimisation.

Display	5.6" color TFT LCD with a 480 x 272 pixel resolution, 16:9 aspect ratio, touchscreen, anti-glare surface
Processor & Memory	372 MHz, Flash ROM 64 Mo et RAM 128 Mo DDR-SD
GPS	Integrated 30-Channel GPS Receiver
Weight & Size	425g & (l x h x p) : 152mm x 97mm x 25mm
Type support	Support of SD cards up to 2 GB
Antenna	Built-in GPS active antenna
Loading temperature	Lithium-Ion Battery:0°... +45°C
Battery	Lithium ion rechargeable battery 2200 mAh for up to 4 hrs. navigation and 2 hrs. of DVB-T
Alimentation	AC 220V/AC 110V DC 10V
Operating Temperature (°C)	-20°C ...+60°C
Other functions	Audio input jack & IR receiver